

KITCHENIO 3-KIT | SURFACE DOWNLIGHT | WHITE **nordlux®**

2015460101



Voltage (V): 230 Volt

IP degree: IP20

Class (Class 1, Class 2, Class 3):

Class 2 (Double isolated)

Socket type: LED – Non-replaceable light source

Height (cm) : 2.1

EAN: 5704924002816

TUN: 2113382

Item Number: 2015460101

Pcs Per Master Carton: 3

Sales Box Height (cm): 9

Sales Box Width (cm): 7

Sales Box Depth (cm): 11

Sales Box Volume m³ : 0.0007

Product net weight (kg): 0.219

Primary material: Plastic

Secondary material: Plastic

Colour: White

Brightness of light (Lumen): 170

Colour temperature (Kelvin):

3000/4000

Ra-value : 80

Lifetime (hours): 25000

Beam angle (°) : 110

Candela (cd) (for directional lamp only): 0

Energy class: G

Actual watt (W): 2.2

- 2-step Moodmaker™ (3000/4000 kelvin) by your regular wall switch • Parallel connection possible • Recessed and surface mounting possible
- Cable included (60 cm) • Long LED lifespan (25,000 hours)

The under-cabinet light Kitchenio is very flexible when it comes to installation as it can easily be recessed, or surface mounted using either screws or double tape. Especially, the included 2 or 4 wire connector block make Kitchenio ready for immediate installation. Equipped with both a 2-step Moodmaker™ and a memory and reset function enables you to change and save your favourite light setting.

The 2-step Moodmaker™ within the Kitchenio under cabinet light enables the possibility to obtain warm light by one single click and cold light by another click on the switch.

www.nordlux.com

